

Product Information

LC 102 - Level Controller 102

Tank contents indicator with remaining volume check

Tank contents measurement up to 9.999 litres

LC 102 is an electronic instrument for indication of tank contents in litres and percentage of tank volume. All common tank shapes are supported. The measurement is done contactless using 40 kHz ultrasonic pulses. The installation is very easy, the probe is connected via a 5 m connection cable.

LC 102 is maintenance free, highly reliable, and is supplied permanently from a mains adapter.

LC 102 is a direct replacement for the mechanical gauges.

Features / Facilities

- Liters of tank volume and percent display
- Ullage in Liters
- Distance to the tank level indicator sensor in cm
- Precise digital display
- Non-contact measurement
- Easy installation on the tank-top
- 2 threaded for screwing.
- Multiple measurements for maximum stability.
- Wall mount application included



LC 102 evaluates the propagation time of ultrasonic pulses to detect the fluid level in the tank. Thus mechanical ageing problems cannot arise. All tank forms in common use are supported like cubic, cylindrical tanks, in horizontal or vertical position. From this information the tank contents in litres is calculated, also the average demand per day and the remaining time period based on average demand is derived.

Applications:

- Heating oil, water tanks, rainwater tanks, waste oil tanks, ...

LC 102 provides the following values:

- Tank contents in litres up to 9.999 litres
- Tank contents in percent of volume
- Remaining empty tank volume in litres – how many litres can be refuelled
- Distance to the fluid surface in cm
- Average demand in litres/day
- Remaining time period in days based on average demand

Product Information

LC 102 - Level Controller 102

Tank contents indicator with remaining volume check

Technical specification

Dimensions (l x w x h):	110 x 85 x 55 mm
Weight (w.o. mains adapter):	Screw thread: 1.5 inch (6/4") and 2 inch app. 380 g
Housing:	colour black, oil resistive
Protection:	IP 20 as per EN 60529
Display:	indoor usage only, in cellars, tank rooms etc. LC-display 51 mm x 35 mm, 2 lines with 4 digits, 12 and 14 mm high
Temperature range:	-10°C ... +45°C
Power supply:	mains adapter 230 V AC with Euro plug

LC 102 is CE-marked and manufactured conform to ROHS requirements.

Measurement method:

Principle:	Ultra-sonic pulses, 40 kHz, pulse duration: 20 ms
Range:	20 cm ... 250 cm (distance to the fluid surface)
Uncertainty:	±1 cm

Installation:

Screw sensor into tank thread 1.5 inch (6/4") and 2 inch
Connect housing wire with sensor plug / (plug diameter 10mm)

Operating modes:


Standard mode:

Every 24 hours a measurement is taken, the tank contents in litres and volume percentage will be displayed permanent.


Manual measurement mode:

A button press initiates a single measurement, an actual tank content is displayed afterwards.


Tank types: Type 1



Type 2



Type 3



Scope of delivery:

LC 102, wall mounting set, mains adapter 230 V AC with Euro plug, measuring sensor with 5 m connection cable, operating instructions

OrderNo.:ST001003

DESIGN & DEVELOPMENT BY



Document: 03 2012 LC E PI 03